

## CLI Asterisk : statistiques des appels

```
pjsip show channelstats
```

```
.....Receive..... ..Transmit.....  
BridgeId ChannelId ..... UpTime.. Codec.  Count   Lost Pct  Jitter  Count   Lost Pct  Jitter RTT....  
=====
```

|          |                   |          |      |     |   |   |       |     |        |         |       |       |
|----------|-------------------|----------|------|-----|---|---|-------|-----|--------|---------|-------|-------|
| 3e3ba5a9 | d65cg0gl-0000c6e5 | 00:00:12 | alaw | 572 | 0 | 0 | 0.030 | 357 | 0      | 0       | 0.004 | 0.047 |
| 3e3ba5a9 | knaxlwql-0000c6e6 | 00:00:12 | alaw | 322 | 0 | 0 | 0.004 | 572 | 16777K | 2933079 | 0.032 | 0.000 |

```
Objects found: 2
```

## CLI Asterisk : liste des peers SIP et leur supervision

```
pjsip list endpoints

Endpoint: <Endpoint/CID.....> <State.....> <Channels.>
=====

Endpoint: kds3g08t/70123          Unavailable  0 of inf
Endpoint: knaxlwql/70060          In use       1 of inf
Endpoint: kr4u8sao/77103          Not in use   0 of inf

Objects found: 3
```

## CLI Asterisk : détail d'un peer SIP

```

pjsip show endpoint ID_LIGNE

Endpoint: <Endpoint/CID.....> <State.....> <Channels.>
  I/OAuth: <AuthId/UserName.....>
  Aor: <Aor.....> <MaxContact>
  Contact: <Aor/ContactUri.....> <Hash....> <Status> <RTT(ms)..>
Transport: <TransportId.....> <Type> <cos> <tos> <BindAddress.....>
Identify: <Identify/Endpoint.....>
  Match: <criteria.....>
  Channel: <ChannelId.....> <State.....> <Time.....>
  Exten: <DialedExten.....> CLCID: <ConnectedLineCID.....>
=====

Endpoint: knaxlwql/70060                               Not in use    0 of inf
  OutAuth: knaxlwql/knaxlwql
  InAuth: knaxlwql/knaxlwql
  Aor: knaxlwql                                         1
  Contact: knaxlwql/sip:knaxlwql@10.27.81.128:5060     d77fd8abee NonQual      nan
Transport: transport-udp                               udp           0    104 0.0.0.0:5060

ParameterName      : ParameterValue
=====
100rel              : yes
CHANNEL(hangup_handler_push) : hangup_handlers,s,1
PICKUPMARK         : 70060%default
TRANSFER_CONTEXT   : default
XIVO_USERID        : 167
XIVO_USERUUID      : e7fabee2-2736-4551-80c5-d75f88056758
accept_multiple_sdp_answers : false
accountcode        :
acl                 :

```